

Cloud ready document processing with Vivid and Vibrant colour output

The imageRUNNER ADVANCE DX C3700i series provides high productivity with excellent colour output quality. The series provide simple and efficient document processing, making it an excellent partner for daily office tasks.



WORKFLOW EFFICIENCY

- Intuitive touchscreen provides users with smartphone-like usability, making navigation a breeze.
- Industry leading Single-Pass document feeder option allows up to 270 ipm scanning, supports paper skew prevention and comes with advanced anti-dust/streak measures.
- My ADVANCE enables a unique, personal experience tailored to meet each user's workflow needs. Settings, such as display language, initial log-in screen, and accessibility options, can be synchronised across multiple devices for consistency.
- Canon's MEAP platform provides process optimisation, by integrating with a range of powerful document, capture and output management solutions.
- Scalable support for mobile where users can connect directly to the device with Direct Access Point. Capture, scan or print documents easily with the Canon Print Business app.
- Intelligent Recovery wakes device from sleep mode when user is approaching device via motion sensor technology.
- Various finishing functions such as Staple-on-Demand, ECO-Staple, saddle stitch, double/corner stapling and foldings are available as an option.

COST MANAGEMENT

- The ability to apply print policies, monitor output, and restrict usage by user helps reduce unnecessary printing, resulting in lower total document cost.
- Seamless integration with output management solutions, such as uniFLOW or uniFLOW Online Express for detailed tracking, reporting and cost analysis.
- Quality and reliability, combined with remote diagnostics and assistance, can help reduce costs by minimising downtime and time spent by IT.
- Consistent user operation combined with remote and centralised fleet management can help simplify IT management of devices and entire fleets.

QUALITY AND RELIABILITY

- V² (Vivid & Vibrant) imaging technology ensures high quality printouts that impress time after time.
- Supreme transferability of toner and stable reproduction of colours onto a wide range of media, even at large volumes.
- State-of-the-art imaging technologies and toner allow for consistently striking images with 1,200 dpi print resolution.
- Canon's device management tools give you a centralised point of control across your entire fleet, upgrade devices remotely, check device and consumables status and capture meter readings.
- Standard PCL and optional Adobe PostScript®3™ print driver allows seamless integration with enterprise applications.
- Remote diagnostics allow timely, accurate and effective resolution.
- Intuitive user maintenance videos and status notifications available to help achieve maximum uptime and keep supplies replenished.

SUSTAINABILITY

- Fusing technologies and innovative sleep mode features help lower overall energy consumption.
- Minimise paper wastage by holding jobs at the device with Force Hold Print. Choose to preview your print jobs or even change print settings at the device to achieve the desired results at the first time of printing.
- Consumes as little as 0.8W in sleep mode.

SECURITY

- Control who has access to the device with different authentication methods such as picture login, department ID, user authentication and card access.
- Ensure information privacy and security across your network with IPsec, port filtering capabilities, and SSL technology.
- Enhance document confidentiality with encrypted secure print, secure print, secure watermark, encrypted PDF and device signature PDF.
- System verification at startup and McAfee® Embedded Control ensures device security, protecting against malware and tampering of firmware.
- Integrate with third-party solutions for complete monitoring protection.

MACHINE SPECIFICATION

MAIN UNIT

Type
A3 Colour Laser Multifunctional

Core Function
Print, Copy, Scan, Send, Store and Optional Fax

Processor
Canon Dual Custom Processor (Shared)

Control Panel
10.1" TFT LCD WSVGA Colour Touch Panel

Memory
Standard: 3.0GB RAM

Hard Disk Drive
Standard*: 320GB (Available Disk Space: 250GB)
Optional : 1TB

*A different initial HDD may be used.

Interface Connection

Network Standard : 1000Base-T/100Base-TX/10Base-T,
Wireless LAN (IEEE 802.11 b/g/n)

Optional : NFC, Bluetooth Low Energy
Others Standard : USB 2.0 x1 (Host), USB 3.0 x1 (Host),
USB 2.0 x1 (Device)

Optional : Serial Interface, Copy Control
Interface

Paper Supply Capacity (A4, 80gsm)

Standard : 1,200 Sheets (2 x 550-sheet cassettes,
1 x 100-sheet multi-purpose tray)
Maximum : 2,300 Sheets (with Cassette Feeding Unit-AP1)

Paper Output Capacity (A4, 80gsm)

Standard : 250 Sheets
Maximum : 3,450 Sheets (with Staple Finisher-AA1/
Booklet Finisher-AA1 and Copy Tray-J2)

Finishing Capabilities

Standard : Collate, Group
With options : Collate, Group, Offset, Staple, Saddle Stitch,
Hole Punch, ECO Staple, Staple-On-Demand

Supported Media Types

Multi-Purpose Tray:
Thin, Plain, Heavy*, Recycled, Coated*, Color, Tracing, Bond,
Transparency, Label, Pre-punched, Envelope

*SRA3 is unsupported for Coated (257-300gsm) and Heavy(257-300gsm)
paper.

Paper Cassette 1:

Thin, Plain, Heavy, Recycled, Color, Bond, Transparency,
Pre-punched, Envelope

Paper Cassette 2:

Thin, Plain, Heavy, Recycled, Color, Bond, Transparency,
Pre-punched, Envelope*

*Envelope Feeder Attachment A (standard) is required.

Supported Media Sizes

Multi-Purpose Tray:
Standard size : SRA3, A3, A4, A4R, A5, A5R, A6R, B4, B5,
B5R, Foolscap, India legal, F4A

Custom size : 98.4 x 139.7 mm to 320.0 x 457.2 mm
Free size : 98.4 x 139.7 mm to 320.0 x 457.2 mm
Envelopes : COM10 No.10, Monarch, ISO-C5, DL
Envelope custom size: 98.0 x 98.0 mm to 320.0 x 457.2 mm

Paper Cassette 1:

Standard size : A4, A5, A5R, A6R, B5
Custom Size : 105.0 x 148.0 mm to 297.0 x 215.9 mm
Envelopes : ISO-C5

Paper Cassette 2:

Standard size : A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R,
Foolscap, India legal, F4A
Custom Size : 105.0 x 148.0 mm to 304.8 x 457.2 mm
Envelopes* : COM10 No.10, Monarch, DL

*Envelope Feeder Attachment A (standard) is required.

Supported Media Weights

Multi-Purpose Tray* : 52 to 300 gsm
Paper 1/2 Cassettes : 52 to 220 gsm
Duplex : 52 to 220 gsm

*SRA3 is unsupported for Coated (257-300gsm) and Heavy(257-300gsm)
paper.

Warm-up Time

Quick Startup Mode : 4 seconds or less*
From Sleep Mode : 10 Seconds or Less
From Power On : 10 Seconds or Less*

*Time from device power-on to when the copy icon appears and is enabled to
operate on the touch panel display.

*Time from device power-on, until copy ready (not print reservation)

Dimensions (W x D x H)

With Platen Cover-Y2 : 565 x 692 x 777 mm
With Single Pass DADF-C1 : 565 x 722 x 887 mm
With DADF-BA1 : 565 x 719 x 880 mm

Installation Space (W x D)

Basic: 978 x 1,118 mm (with Single Pass DADF-C1 + right
cover open + Multi-purpose tray extension extended
+ paper cassette open)
978 x 1,115 mm (with DADF-BA1 + right cover open +
Multi-purpose tray extension extended + Paper
cassette open)

Fully Configured:
1,651 x 1,118 mm (with Single Pass DADF-C1 +
Staple Finisher-AA1/Booklet Finisher-AA1 +
Copy Tray-J2 extension extended + paper cassette
open)
1,651 x 1,115 mm (with DADF-BA1 + Staple Finisher-
AA1/Booklet Finisher-AA1 + Copy Tray-J2 extension
extended + paper cassette open)

Weight

With Platen Cover-Y2 : Approx. 66.7 kg including toner
With DADF-BA1 : Approx. 73.1 kg including toner
With Single Pass DADF-C1 : Approx. 79.6 kg including toner

Printing Specifications

Print Speed (BW and CL)

iR-ADV DX C3730i up to 30ppm (A4/A5/A5R/A6R)

up to 15ppm (A3)
up to 20ppm (A4R)

iR-ADV DX C3725i up to 25ppm (A4/A5/A5R/A6R)
up to 15ppm (A3)

up to 20ppm (A4R)

iR-ADV DX C3720i up to 20ppm (A4/A5/A5R/A6R)
up to 15ppm (A3)

up to 20ppm (A4R)

Print Resolution (dpi)

600 x 600, 1,200 x 1,200 (half speed)

Page Description Languages

Standard : UFR II, PCL6
Option : Adobe® PostScript®3™

Direct Print

Supported file types: PDF, EPS, TIFF/JPEG, and XPS

Printing from Mobile and Cloud

AirPrint, Mopria, Google Cloud Print, Canon Print Business,
and uniFLOW Online

Fonts

PS fonts : 136 Roman
PCL fonts : 93 Roman, 10 Bitmap fonts, 2 OCR fonts,
Andalé Mono WT J/K/S/T*1 (Japanese, Korean, Simplified
and Traditional Chinese), Barcode fonts*2

*1 Requires optional PCL International Font Set-A1

*2 Requires optional Barcode Printing Kit-D1

Operating System

UFR II: Windows® 7/8.1/10/Server 2008/Server 2008 R2/
Server 2012/Server 2012 R2/Server 2016/Server 2019,
MAC OS X (10.10 or later)

PCL: Windows® 7/8.1/10/Server 2008/Server 2008 R2/
Server 2012/Server 2012 R2/Server 2016/Server 2019

PS: Windows® 7/8.1/10/Server 2008/Server 2008 R2/
Server 2012/Server 2012 R2/Server 2016/Server 2019,
MAC OS X (10.10 or later)

PPD: Windows® 7/8.1/10, MAC OS X (10.9 or later)

Copy Specifications

Copy Speed (Bw and CL)

iR-ADV DX C3730i up to 30ppm (A4/A5/A5R/A6R)

up to 15ppm (A3)
up to 20ppm (A4R)

iR-ADV DX C3725i up to 25ppm (A4/A5/A5R/A6R)

up to 15ppm (A3)
up to 20ppm (A4R)

iR-ADV DX C3720i up to 20ppm (A4/A5/A5R/A6R)

up to 15ppm (A3)
up to 20ppm (A4R)

First-Copy-Out Time (A4, BW/CL)

Approx. 5.9/8.2 seconds or less

Copy Resolution (dpi)

600 x 600

Multiple Copies : Up to 999 copies

Copy Exposure : Automatic or Manual (9 Levels)

Magnification : Variable zoom

: 25% to 400% (1% Increments)

Preset reduction/enlargement:
25%, 50%, 61%, 70%, 81%, 86%,
100% (1:1), 115%, 122%, 141%,
200%, 400%

Scan Specifications

Type

Standard: Colour Flatbed Scan Unit

Optional: Platen Cover, Single Pass DADF-C1* or DADF-BA1
[2-sided to 2-sided (Automatic with DADF)]

* Detect Feeder Multi Sheet Feed is supported.

Document Feeder Paper Capacity (80gsm)

Single Pass DADF-C1 : up to 200 Sheets
DADF-BA1 : up to 100 Sheets

Acceptable originals and weights

Platen: Sheet, Book, and 3-Dimensional Objects
Document Feeder media weight:

Single Pass DADF-C1:

1-sided scanning: 38 to 220 gsm (BW, CL)

2-sided scanning: 38 to 220 gsm (BW, CL)

*An acceptable weights of A6R or smaller is 50 to 220gsm.

DADF-BA1:

1-sided scanning: 38 to 128 gsm (BW), 64 to 128 gsm (CL)

2-sided scanning: 50 to 128 gsm (BW), 64 to 128 gsm (CL)

Supported Media Sizes

Platen max. scanning size: up to 297.0 x 431.8 mm
Single Pass DADF-C1: A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, B6R,

Custom size: 70.0 x 139.7 mm to 304.8 x 431.8 mm

DADF-BA1: A3, A4, A4R, A5, A5R, B4, B5, B5R, B6,

Custom size: 139.7 x 128 mm to 297.0 x 431.8 mm

Scan Speed (ipm, BW/CL, A4)

Single Pass DADF-C1:

1-sided Scanning: 135/135 (300 x 300 dpi, send),

51/51 (600 x 600 dpi, copy)

2-sided Scanning: 270/270 (300 x 300 dpi, send),

51/51 (600 x 600 dpi, copy)

DADF-BA1:

1-sided Scanning: 70/70 (300 x 300 dpi, send),

51/51 (600 x 600 dpi, copy)

2-sided Scanning: 35/35 (300 x 300 dpi, send),

25.5/25.5 (600 x 600 dpi, copy)

Scan Resolution (dpi)

Scan for Copy: 600 x 600

Scan for Send: (Push) 600 x 600 (SMB/FTP/WebDAV/IFAX),

(Pull) 600 x 600

Scan for Fax: 600 x 600

Pull Scan Specifications

Colour Network ScanGear2. For both TWAIN and WIA

Supported OS: Windows® 7/8.1/10/Server 2008/Server 2008 R2/Server 2012/Server 2012 R2/Server 2016

Send Specifications

Destination

Standard : E-mail/Internet FAX (SMTP), SMB3.0, FTP, WebDAV, Mail Box

Optional : Super G3 FAX, IP Fax

Address Book

LDAP (2,000)/Local (1,600)/One-touch (200)

Send Resolution (dpi)

Push : up to 600 x 600

Pull : up to 600 x 600

Communication Protocol

File : FTP (TCP/IP), SMB 3.0 (TCP/IP), WebDAV

E-mail/I-Fax : SMTP, POP3

File Format

Standard : TIFF, JPEG, PDF (Compact, Searchable, Apply policy, Optimize for Web, PDF/A-1b, Trace & Smooth, Encrypted, Device Signature, User Signature), XPS (Compact, Searchable, Device Signature, User Signature), Office Open XML (PowerPoint, Word)

Fax Specifications

Maximum Number of Connection Lines 2

Modem Speed Super G3 : 33.6 kbps
G3 : 14.4 kbps

Compression Method MH, MR, MMR, JBIG

Resolution (dpi) 400x400 (Ultra Fine),
200x400 (Super Fine),
200x200 (Fine),
200x100 (Normal)

Sending/Receiving Size

Sending : A3, A4, A4R, A5¹, A5R¹, B4, B5², B5R¹

Receiving : A3, B4, A4, A4R, A5R, B5, B5R

^{*1} Sent as A4 ^{*2} Sent as B4 short

FAX Memory Up to 30,000 pages (2,000 jobs)

Speed Dials Max. 200

Group Dials/Destinations Max. 199 dials

Sequential Broadcast Max. 256 addresses

Memory Backup Yes

Store Specifications

Mail Box Simple (Number supported)

100 User Inboxes, 1 Memory RX Inbox,

50 Confidential Fax Inboxes

Maximum 10,000 Pages (2,000 jobs) Stored

Advanced Box

Communication Protocol: SMB or WebDAV

Supported Client PC: Windows® 8.1/10

Concurrent Connections (Max.): SMB: 64, WebDAV: 3

Advanced Box available disc space

Approx. 16GB (Standard HDD)

Approx. 480GB (with option 1TB HDD)

Security Specifications

Authentication and Access Control

Standard : User Authentication (Picture Login, Picture and PIN Login, Card Login, Username and Password Login, Function Level Login, Mobile Login), Department ID Authentication (Department ID and PIN Login, Function Level Login), uniFLOW Online Express (PIN Login, Picture Login, Picture and PIN Login, Card Login, Card and PIN Login, Username and Password Login, Department ID and PIN Login, Function Level Login), Access Management System (Access Control)

Document Security

Print Security (Secure Print, Encrypted Secure Print, Forced Hold Printing, uniFLOW Secure Print^{*1})

Receive Data Security (Confidential Fax Inbox Forwarding Received Documents Automatically)

Scan Security (Encrypted PDF, Device Signature PDF/XPS, User Signature PDF/XPS, Adobe LiveCycle® Rights Management ES2.5 Integration), BOX Security (Mail Box Password Protected, Advanced Box Access Control)

Send Data Security (Setting for requesting password input per transmission, Restricted E-mail/File send functions, Confirming FAX number, Allow/Restrict Fax Driver Transmissions, Allow/Restrict Sending from History, S/MIME Support), Scan Lock (QR code), Document Tracking (Secure Watermark)

^{*1} Requires uniFLOW Online/uniFLOW

Network Security

TLS 1.3, IPsec, IEEE802.1X authentication, SNMP V3.0, Firewall Functionality (IP/MAC Address Filtering), Dual Network Support (Wired LAN/Wireless LAN, Wired LAN/Wired LAN), Disabling Unused Functions (Enabling/Disabling Protocols/Applications, Enabling/Disabling Remote UI, Enabling/Disabling USB Interface)

Device Security

Protecting HDD Data (HDD Data Encryption (FIPS140-2 Validated), HDD Data Overwrite Erase, HDD Lock), Standard HDD Initialize, Trusted Platform Module (TPM), Job Log Conceal Function, Protecting MFD Software Integrity, Checking MFD Software Integrity (Verify System at Startup, Runtime Intrusion Detection), Optional: IEEE2600.2 (Common Criteria Certification) (available at a later schedule)

Device Management and Auditing

Administrator Password, Digital Certificate And Key Management, Audit Log, Cooperating with External Security Audit System (Security Information and Event Management), Image Data Logging, Security Policy Setting

Environment Specifications

Operating Environment

Temperature: 10 to 30 °C

Humidity: 20 to 80 % RH (Relative Humidity)

Power Requirements

220-240V, 50/60Hz, 4A

Power Consumption

Maximum: 1,500 W

Standby: Approx. 45.1 W^{*1}

Sleep mode: Approx. 0.8 W^{*2}

^{*1} Reference Value

^{*2} 0.8W sleep mode is not available in all circumstances due to certain settings.

Consumables

Toner Cartridge NPG-67 Toner BK/C/M/Y

Toner Yield (Estimated Yield @5% Coverage)

NPG-67 Toner BK : 36,000 pages

NPG-67 Toner C/M/Y : 19,000 pages

NPG-67L Toner C/M/Y : 2,500 pages

Software and Printer Management

Tracking and reporting

Universal Login Manager (ULM)

uniFLOW Online Express

Remote Management Tools

iW Management Console

eMaintenance

Content Delivery System

Scanning Software

Network ScanGear

Optimisation Tools

Canon Driver Configuration Tool

NetSpot Device Installer

Platform

MEAP (Multifunctional Embedded Application Platform)

Document Publishing

IW DESKTOP

Paper Supply Options

CASSETTE FEEDING UNIT-API

Paper Capacity : 550 sheets x 2 (1,100 sheets, 80 gsm)

Paper Type : Thin, Plain, Recycled, Color, Heavy Bond, Transparency, Pre-punched

Paper Size : A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, Foolscap, India Legal, F4A

Custom size : 105.0 x 148.0 mm to 304.8 x 457.2 mm

Paper Weight : 52 to 220 gsm

Power Source : From the Main Unit

Dimensions : (WxDxH) 565 x 615 x 248 mm

Weight : Approx. 16.0 kg

Hardware Accessories

Card Readers

COPY CARD READER-F1

COPY CARD READER ATTACHMENT-B7

Others

UTILITY TRAY-B1

NUMERIC KEYPAD-A1

PLATEN COVER-Y2

3 WAY UNIT-D1

Security Options

Device Security

IR-ADV SECURITY KIT-AM1 FOR IEEE 2600 COMMON CRITERIA CERTIFICATION (available at a later schedule)

Data Security

2.5INCH/1TB HDD-P1

System and Controller Options

Print Accessories

PCL INTERNATIONAL FONT SET-A1

PCL ASIAN FONT SET-A1

PS PRINTER KIT-BJ1/CD1

Barcode Printing

BARCODE PRINTING KIT-D1

System Accessories

SERIAL INTERFACE KIT-K3

COPY CONTROL INTERFACE KIT-A1

CONNECTION KIT-A2 FOR BLUETOOTH LE

NFC KIT-E1

Fax Accessories

SUPER G3 FAX BOARD-AZ1

SUPER G3 2ND LINE FAX BOARD-AU1

REMOTE FAX KIT-A1

IP FAX EXPANSION KIT-B1

Other Options

Accessibility Accessories

ADF ACCESS HANDLE-A1

VOICE GUIDANCE KIT-G1

VOICE OPERATION KIT-D1

Staple Cartridge

STAPLE-P1

STAPLE CARTRIDGE-Y1

For full specifications, please refer to the specification table on your local Canon web site.

MAIN CONFIGURATION OPTIONS



BOOKLET FINISHER-AA1

- 2-tray, 3,250 -sheet capacity
- Corner and double stapling up to 50 sheets (80 gsm)
- Booklet-making up to 20 sheets and non-staple saddle folded capacity up to 3 sheets (A3/A4R)
- Supports ECO-Staple 4 sheets (80 gsm) and Staple-On-Demand 50 sheets (80 gsm)
- Supports optional external 2/3 and 2/F4 hole punchers (2/3H PUNCHER UNIT-A1 and 2/F4H PUNCHER UNIT-A1)



STAPLE FINISHER-AA1

- 2-tray, 3,250 -sheet capacity
- Corner and double stapling up to 50 sheets (80 gsm)
- Supports ECO-Staple 4 sheets (80 gsm) and Staple-On-Demand 50 sheets (80 gsm)
- Supports optional external 2/3 and 2/F4 hole punchers (2/3H PUNCHER UNIT-A1 and 2/F4H PUNCHER UNIT-A1)



INNER 2 WAY TRAY-J1

- Separates copies, prints and faxes
- Adds a second internal output tray



INNER FINISHER - K1

- 2-tray, 600 -sheet capacity
- Corner and double stapling up to 50 sheets (80 gsm)
- Supports ECO-Staple 4 sheets (80 gsm) and Staple-On-Demand 40 sheets (80 gsm)



PLATEN COVER Y2

- Single document scanning



DADF - BA1

- Multiple document scanning
- 100-sheet duplexing automatic document feeder
- Scans up to 70 ipm (1-sided, 300 dpi) and 35 ipm (2-sided, 300 dpi)




SINGLE-PASS DADF-C1

- Multiple document scanning
- 200-sheet duplexing automatic document feeder
- Scans up to 135 ipm (1-sided, 300 dpi) and 270 ipm (2-sided, 300 dpi)



UTILITY TRAY B1



COPY TRAY-J2



CASSETTE FEEDING UNIT-API

- Supports up to A3
- Media weight 52 -220 gsm
- 2 x 550 sheets (80 gsm)

METAL PEDESTAL 35/30

Raises the device, no additional media supply



V² COLOUR



Partner/Dealer Stamp

CITI OFFICE MACHINE SDN. BHD. (372258-M)
40, Jalan Perusahaan Jelutong 2,
11600 Jelutong, Penang.
Tel : 04-283 1010 Fax : 04-283 3030
Email : citioffice1010@gmail.com

To arrange for a demonstration, simply contact any of our offices below.

**SOUTH & SOUTHEAST ASIA
REGIONAL HEADQUARTERS**

Canon Singapore Pte. Ltd. | 1 Fusionopolis Place #15-01 Galaxis Singapore 138522
 Tel: 65-6799 8888 | Fax: 65-6799-8882 | www.canon-asia.com | www.canon.com.sg

This document is for general information only and contents are subject to change without notice. Errors and omissions excepted. Weights and dimensions are approximates. Options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations in connection with this document. Trademarks belong to their respective owners.

Canon, imageRUNNER, imageRUNNER ADVANCE, imageCHIP, RAPID Fusing System, MEAP, eMaintenance, iW, Business can be simple and get Smart get genuine are trademarks of Canon Inc. and/or its affiliates. "MEAP" is a trademark of CANON Inc., referring to an "application platform" for Canon multifunction and single function printers. Other names may be the trademarks of their respective owners. uniFLOW, eCopy and Therefore are independent party software distributed by Canon Singapore Pte Ltd.

Adobe, PostScript, PostScript 3 and the PostScript logo are trademarks of Adobe Systems Incorporated

0220W283 @ 2020 Canon Singapore Pte. Ltd.
 All rights reserved. Printed in Singapore.