

imagePROGRAF
TM-5200 | TM-5205

Canon
Delighting You Always

Performance in A Whole New Dimension



Quiet, Fast, Precise

The all-new imagePROGRAF TM-5200 and TM-5205 redefine printer excellence. Boost your workplace productivity with software applications that seamlessly manage and simplifies your print jobs. Featuring an all-new pigment LUCIA TD ink with superb print quality for line and text reproduction and vibrant poster prints. Boasting an impressive 44dB acoustic sound level, the TM-5200 and TM-5205 truly lives up to the ideal that your prints should be seen, not heard.

SPECIFICATIONS

PRINTER	TM-5200	TM-5205
Printer Type	5 Colour 24"	
Number of Nozzles	15,360 nozzles (MBK: 5,120 nozzles; BK, C, M, Y 2,560 Nozzles each)	
Print Resolution (Max)	2400 x 1200dpi	
Nozzle Pitch	1200dpi (2lines)	
Line Accuracy	±0.1 % or less	
Ink Droplet Size	Minimum 5 Picoliter per colour	
Ink Capacity	130ml/300ml (MBK, BK, C, M, Y) Bundled Starter Ink: 130ml (MBK)/ 90ml (BK, C, M, Y)	
Ink Type	Pigment inks/ 5 colour MBK, BK, C, M, Y	
Printer Languages	SG Raster (Swift Graphic Raster), HP-GL/2, HP RTL, JPEG (Ver JFIF1.02)	SG Raster (Swift Graphic Raster), HP-GL/2, HP RTL, PDF (Ver 1.7), JPEG (Ver JFIF1.02)
Standard Interfaces	USB B Port Built in (High-Speed USB), Full Speed (12 Mbit/sec), High Speed (480 Mbit/sec), Bulk Transfer, Series B (4 pins);	
	Not Available	USB A Port USB Memory (Direct Print);
	Gigabit Ethernet Built in, IEEE 802.3 10base-T, IEEE 802.3u 100base-TX/ Auto-Negotiation, IEEE 802.3ab 1000base-T/ Auto-Negotiation, IEEE 802.3x Full Duplex, SNMP (Canon-MIB, HTTP, TCP/IP(IPv4/IPv6), ftp;	
	Wireless LAN IEEE802.11n/ IEEE 802.11g/ IEEE 802.11b, WEP (64/128bit), WPA-PSK (TKIP/AES), WPA2-PSK (TKIP/AES)	
Memory	Standard Memory 2GB	Standard Memory 128GB (Physical Memory 2GB)
Hard Disk	Not Applicable	500GB
PRINTING SPEED (A1 SIZE)		
Plain Paper (CAD Drawings)	00:24 Fast (Custom Q5) 00:27 Fast 00:42 Standard	
Heavyweight Coated Paper HG (CAD Drawings)	00:29 Fast (Custom Q5) 00:40 Fast 01:17 Standard	
Plain Paper (Poster)	00:25 Fast (Custom Q5) 00:25 Fast 00:44 Standard	
Heavyweight Coated Paper HG (Poster)	00:55 Fast 01:22 Standard	
MEDIA HANDLING		
Media Width	Roll Paper/Cut Sheet: 203.2~610mm	
Media Thickness	Roll Paper/Cut Sheet: 0.07~0.8mm	
Minimum Printable Length	Roll Paper: 203.2mm, Cut Sheet: 279.4mm	
Maximum Printable Length	Roll Paper: 18m (Varies according to the OS and application), Cut Sheet: 1.6m	
Maximum Media Roll Outer Diameter	150mm or less	
Paper Feed Method	Roll Paper: One Roll, Upper-loading, Front Output; Cut Sheet: Upper-loading, Front Output (Manual feed using media locking lever)	
Borderless Printing Width (Roll Only)	Recommended 515mm (JIS B2), 594 mm (ISO A1), 10", 14", 17", 24"	
	Printable 257mm (JIS B4), 297 mm (ISO A3), 329mm (ISO A3+), 420mm (ISO A2), 8", 12", 16", 20", 300mm, 500mm, 600mm	
Media Output (SD-23)	Standard Position: 1 Sheet Folding Position: 20 sheets on A1 portrait, Flat Position: 20 sheets on A2 landscape	

PRINTER	TM-5200	TM-5205
DIMENSIONS & WEIGHT		
Packaged Dimensions W x D x H (mm) / Weight (kg)	Printer (Main Unit with Pallet) 1152 x 913 x 705mm, Weight: 69kg	
	Stand + Basket (SD-23) 1155 x 824 x 268mm, Weight: 18kg	
	Printer (Main Unit with Stand SD-23 and Pallet) 1152 x 913 x 961mm, Weight: 87kg	
Physical Dimensions W x D x H (mm) / Weight (kg)	Main Unit + Stand + Basket (SD-23) Basket Opened: 982 x 887 x 1060mm Basket Closed: 982 x 757 x 1060mm Weight: 52 kg (including Roll Holder Set, excluding ink and print head)	
POWER AND OPERATING REQUIREMENTS		
Power Supply	AC 100-240V (50-60Hz)	
Power Consumption	Operation: 69W or less; Sleep Mode: 3.6W or less; Power Off: 0.3W or less	
Operating Environment	Temperature: 15°C~30°C, Humidity: 10%~80% RH (no dew condensation)	
Acoustic Sound	Acoustic Power Operation: 6.0 Bels (Plain paper, line drawing, standard mode) (Measured on ISO7779 standard)	
	Acoustic Pressure Operation: 44dB(A) (Plain paper, line drawing, standard mode) Standby : 35dB(A) or less (Measured on ISO7779 standard)	
OPTIONS		
2/3" Roll Holder	RH2-28	
CONSUMABLES		
Ink Tank	PFI-8120 (130ml)/ PFI-8320 (300ml)	
Print Head	PF-06	
Cutter Blade	CT-08	
Maintenance Cartridge	MC-31	
SCANNER*		
Scan Width	24"	Not Available
Min Scan Width	6.2" (16cm)	
Max Scan Length	109" (2768mm)	
Max Scan Speed (Inches/second)	Copy Draft: 300/300dpi, 1ips (Col), 3ips (B&W) Standard: 300/600dpi, 1ips (Col), 3ips (B&W) Best: 600/600dpi, 0.5ips (Col), 1.5ips (B&W)	
	Scan Draft: 200dpi, 1ips (Col), 3ips (B&W) Standard: 300dpi, 0.5ips (Col), 1.5ips (B&W) Best: 600dpi, 0.33ips (Col), 1ips (B&W)	
Optical Resolution	600dpi	
Max Document Thickness	0.5mm	
Software Included	ScanApp Lei Software	
Software Features	Scan, Copy, JPG, PDF, PDF/A, Multipage PDF file formats, Scan to PC, Scan to USB	
Dimension W x D x H (mm) / Weight (kg)	935 x 253 x 131mm / 5.28kg	

*Scanner is manufactured by U.K.-based Global Scanning UK Ltd.

Canon
Delighting You Always

CANON SINGAPORE PTE. LTD.
1 Fusionopolis Place, #15-10 Galaxis, Singapore 138522
Tel : 65-6799-8888 | Fax : 65-6799-8882 | www.canon-asia.com



SCAN HERE
FOR MORE INFO



TARGET Sign Tech Pvt. Ltd.

Kalash-2 Complex Basement, Nr. Jain Derasar, B/h.Navrangpura Post Office, A'bad-09. Gujarat.

Distributors : Supratech, Roland Ecosol, Colorjet Solvent, Canon, Ricoh, Habit Mug Combo

T : +91-79-66612961/2 M.: 98240 77124 / 93773 77124

E : targethabit@gmail.com Website : www.targetsigntech.com, www.supratechindia.com